

Attachment for Warehouse Forklifts

Warehouse Forklift Attachments - Pneumatic jacks are often called pallet trucks or pump trucks and are widely used in warehouses and shipping plants to transport resources on pallets. Pneumatic jacks include a pair of steel forks installed on a wheeled counterweight that contains a pump. The pump is used to lift and lower the blades.

Visually inspect the pallet lift before loading. Make sure the wheels are free of any would-be obstructions. Furthermore, ensure the handle moves fluently and turns appropriately. Check the pallet prior to moving it to assess if it is stacked in a way that minimizes the chance of anything falling off during lifting. Release any air in the pump and drop the forks to the floor by squeezing the handle installed on the inside of the metal loop on the end of the lever. Run the blades into the slots in the pallet and make sure the forks are centered so that the pallets' weight is evenly distributed.

By pumping the pneumatic jack lever the blades will ascend from the ground. Once there is full clearance, you can stop pumping as there is no need to raise the hoist anymore. To move the pallet lift, you can drag the handle behind you. It is not recommended to push the pallet lift. There will be a large amount of momentum present. Avoid quick or sharp turns and do not stop too swiftly. Gently bring the pallet to a rest wherever you would like to park it. Squeeze the lever inside the grip end to return the blades to the ground. Withdraw the forks and restore the pallet lift to an appropriate parking area or continue onto the next undertaking.